MEMOR™ 10 HEALTHCARE

ODATALOGIC



MEMOR™ 10 - THE POWER OF A SMARTPHONE, DESIGNED FOR **ENTERPRISE**

If you are looking for the power and the performance of a smartphone but are concerned about the typical Enterprise challenges, the new Datalogic Memor 10 PDA is the perfect rugged device for you!

Memor 10 incorporates the latest smartphone technologies and the user friendly experience of Android™ in a slim and compact design, combined with high performance 1D/2D bar code scanning and industrial robustness for almost any indoor or outdoor environment.

TOP PERFORMANCE

The Memor 10 is powered by a superior octa-core platform clocked at 2 GHz for top performance with the most demanding applications, and features Android 8.1 (Oreo) with Google Mobile Services (GMS).

Moreover, the Memor 10 is one of the first rugged mobile computers to be validated by Google for the 'Android Enterprise Recommended' program for rugged devices.

WIRELESS CHARGING MEETS SWAPPABLE BATTERY

The Memor 10 incorporates Datalogic's industry-first wireless charging system for ultra-reliable contactless charging, thus eliminating the need for cleaning contacts on the device and docks. Moreover, Memor 10 offers a 1-piece swappable battery for the best operational advantage.

DESIGNED FOR HEALTHCARE

The Memor 10 has a complete fit for the Healthcare industry and embeds a chemical resistant enclosure to withstand daily cleaning with harsh disinfectant solutions. Dedicated accessories such as the battery pack and handstrap are designed to have cleaning procedures as well.

NOTE: The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

FEATURES

- · Ultra-Ergonomic, compact and robust
- 5 inch capacitive multi-touch HD display with Dragontrail™ hardened glass
- Android 8.1 (Oreo) with Google Mobile Services
- · Wireless charging eliminates all contacts on the device and cradle
- Ruggedized with drop resistance to 1.5m / 5ft to concrete and IP65 sealing
- Dual band Wi-Fi including the latest 802.11ac standard and 802.11r/k for fast roaming
- Full suite of cellular connectivity for voice and data, featuring LTE-Advanced/4G+
- Assisted GPS for location based apps
- Bluetooth v4.2 short range wireless technology
- NFC for proximity communications
- · Advanced 2D ultra-slim imager with Datalogic's patented 'Green Spot' technology for visual good-read feedback
- Datalogic's SoftSpot™ technology for innovative triggering through the touch display
- Chemical resistant plastics / enclosure designed to withstand daily cleaning with harsh disinfectant solutions
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

Industry - Application

- Retail:
 - Assisted sales
 - Inventory
 - Access control
 - Shop floor applications
 - Mobile POS
- - Route accounting
 - Direct store delivery
 - Workforce management
 - Courier value-added services
- Manufacturing:
 - Production and quality control
 - Intra-logistics
 - Inventory
 - Field maintenance
- Healthcare:
 - Bedside care
 - Pharmacy
 - Inventory management
 - Labs

















MEMOR™ 10 HEALTHCARE

TECHNICAL SPECIFICATIONS

WIRELESS COMMUNICATIONS		
Local area network (WLAN)	IEEE 802.11 a/b/g/n/ac and 802.11 k/r/v; Frequency range: Country dependent, typically 2.4GHz and 5GHz bands	
Personal area network (WPAN)	Bluetooth wireless technology v4.2 (Classic Bluetooth wireless technology and BLE)	
Ncf Communication	Support for the following standards: ISO14443-4 (type-A, type-B); ISO15693; Mifare; Felica	
WWAN / cellular	LTE-Advanced/4G+; Cat 6	

DECODING CAPAB	
1D / linear codes	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D codes	Aztec Code, Data Matrix, HanXin Code, MaxiCode, MicroQR Code, QR Code, UPU FICS, USPS Intelligent Mail
Postal codes	Australian Post, Japan Post, KIX Code, PLANET, POSTNET, Royal Mail Code (RM4SCC)
Stacked Codes	Micro-PDF417, PDF417, GS1 DataBar Composites, GS1 DataBar Expanded Stacked, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional
ELECTRICAL	
Battery	Replaceable battery pack with rechargeable Li-Ion batteries; 3.8v; 4,100 mAh (15.6 Watt-hours)
Wireless charging	Qi Compliant; 10 Watt fast charging
ENVIRONMENTAL	
Drop resistance	Withstands drops from 1.5 m / 5.0 ft onto concrete (with rubber boot); Withstands drops from 1.2 m / 4.0 ft onto concrete (without rubber boot). Tested onto steel/concrete according to IEC 68-2-32 Method 2 and MIL STD 810G Transit drop test.
Tumbles	Withstands 1000 hits from 0.5 m / 1.6 ft and 250 hits from 1.0 m / 3.2 ft per IEC 600-2-32 with rubber boot; Withstands 600 hits from 0.5 m / 1.6 ft per IEC 600-2-32 without rubber boot
Particulate and water sealing	IP65
Chemical resistance	Chemical cleanser and industrial oil resistant (both Standard and Healthcare models)
Healthcare cleanable	Isopropyl Alcohol, Hydrogen Peroxide, Clorox® Bleach; applicable for both the device and cradles
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -30 to 70 °C / -22 to 158 °F
INTERFACES	
Interfaces	High Speed USB 2.0 Host and Client with USB Type C connector
SENSORS	
Vibration	Software programmable for duration and intensity
Accelerometer	3-Axis accelerometer to detect orientation
Gyroscope	Senses angular velocity
Ambient light	Auto adjusts display backlight
Proximity	Auto deactivates display when close to face

	ILINIO I I CO	
Dimensions	15.5 x 7.8 x 1.87 cm / 6.1 x 3.07 x 0.73 in	
Display	5 inch IPS HD resolution 720 x 1280; LED backlight; Touch Screen: 5 points multi-touch capacitive panel with Dragontrail hardened glass	
Keys	Physical Keys: 2 side scan keys; Power On/Off; Volume Up/Down; 3 user programmable Android™ keys	
Weight	With Battery: 285.0 g / 10.0 oz	
READING PERFORMANCE		
Camera	Resolution: 13 megapixel; Illumination: User controllable LED flash; Lens: Auto focus	
Scan engine	2D Ultra slim area imager (supports 1D / 2D codes); Datalogic's 'Green Spot' for good-read feedback; Depth of Field: 8.5 to 50 cm / 3.3 to 19.7 in depending on bar code density and type; Resolution: VGA (640 x 480 pixels); Illumination: White LEDs; Aiming: 650nm VLD; Field of View: 48°H x 34°V	
Print contrast (minimum)	25%	
Minimum element width	1D Linear: 0.0762 mm / 4 mils PDF: 0.127 mm / 6.6 mils Data Matrix: 0.195 mm / 7.5 mils	
SAFETY & REGULATORY		
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.	
Environmental Compliance	Complies to EU RoHS	
SOFTWARE		
Applications	Datalogic's SoftSpot technology for configurable soft triggers; Supports Datalogic's Queue Busting app; Pre-licensed device and browser lockdown powered by 42Gears; Enterprise class PTT offered by Zello	
Provisioning	Android Zero Touch enrollment and QR Code or NFC Bump provisioning	
Configuration and maintenance	Datalogic DXU for device configuration and firmware upgrade from PC	
Development	Java and Xamarin SDK available	
MDM	SOTI MobiControl, VMWare AirWatch, Wavelink Avalanche, 42Gears SureMDM	
Terminal emulation	StayLinked SmartTE, Wavelink Velocity	
SYSTEM		
Expansion slots	Micro-SD card slot: Compatible with Micro SD-HC cards; Data transfer up to 48 Mbps; User-accessible	
Memory	System RAM: 3 GB; eMMC Flash: 32 GB	
Microprocessor	2 GHz Octa-core	

Android v8.1 with GMS

1-Year Factory Warranty

Time and date stamping under software control

ACCESSORIES

Base Stations/Chargers



94A1500958

Single Slot Dock



94ACC0205 Cleanable Battery Pack

Miscellaneous





94ACC0204 Rubber Boot

94ACC0203 Cleanable Handstrap

Operating System

Reak-time clock

Warranty

© 2017-2018 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • Skorpio is a trademark of Datalogic S.p.A. and/or its affiliates, registered in the E.U. • Android is a trademark of Google Inc. • The Bluetooth word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners • Product specifications are subject to change without notice. • DS-SKORPIOX4-ENA4 Revision C 20180226